



SEMI AUTOMATIC TIN TIE APPLICATOR



2200 SERIES

Model LX2200 or RX2200 "Tin Tie" machine to place .315" wide, double wire tin tie, on bag faces of filled bags. Filled bags would normally be pre-sealed. The tin tie is applied using a hot melt adhesive.

APPLIES TIN TIE RECLOSURES TO:

- Filled Bags
- Paper Bags
- Film Bags
- Pouches
- Multi Wall Bags
- Empty Bags





SEMI AUTOMATIC TIN TIE APPLICATOR

FEATURES

Fully adjustable floor stand to adjust machine height

Nordson hot melt adhesive system

Single spool payout system to accept 6000 foot spools of .315" wide 23 or 24 guage "tin tie".

Automatically applies tin tie and adjusts tab length to bag face width.

High Speed Programmable Logic Controller

Right or left hand directional feed

Continuous motion for smooth flow

Made in America

SPECIFICATION

Electrical 240 VAC, 15 AMP 1 phase

Pneumatic 80 psi

Wired to National Electrical Code

Bag face width range 3 to 12 inches

Bag height range 4 to 18 inches

Bag thicknesses up to 6 inches

Patent number 4,420.355

Tie tab length from 0.8 to 1.2 inches

80 bags per minute with 5 inch tie length

Standard 34 inch height mounted conveyor

ADDITIONAL OPTIONS

Different voltages upon request

