Streamlining Production Through Automation[™]



MS-30T CASE SEALER



MS-30T CASE SEALER

THE MASSMAN MS-30T SMALL FOOTPRINT TOP TAPE CASE SEALER OPERATES AT SPEEDS UP TO 30 CASES/ MINUTE. SUPERIOR PUSHER BAR CASE SQUARING THROUGH MACHINE TRANSFER SYSTEM, PLC

CONTROLLED, NO CASE, NO KICK, FLAP TUCKER, FULLY GUARDED, CAT 3 CONTROLLED INTERLOCK ACCESS DOORS, ROBUST CONSTRUCTION, AND SERVICE

BEHIND THE SALE ARE JUST A FEW BENEFITS OF THIS MACHINE.





MS-30T CASE SEALER

FEATURES	SPECIFICATION	ADDITIONAL OPTIONS
Up to 30 Cases per Minute-Standard	Electrical-460/230 3 Phase	Casters, Leveling Feet
* Please note these rates can vary depending on style and size of case	20 AMP	Taller than Long Cases
Standard Case Range	NEMA 12 Standard	Square Cases
Length 8" to 23"		Outside Standard Range Cases
Width 6 1/2 " to 16"		Stainless Steel Components
Depth 4 /2" to 16"		NEMA 4 Controls
High Speed Case Sealer		Hot Glue Closure
Superior Case Squaring Transfer System		Top and Bottom Sealing
Small Footprint Top Tape Sealer		
Fully Guarded Interlock Door Access		
Category 3 Safety		
Drop Gate or Powered Belt Case Metering at Infeed		
Single Side Adjustment Points for Fast Changeover		
No Case, No Kick, Flap Tucker		



Massman Automation Designs, LLC 1010 East Lake Street, Villard, MN 56385 Call 320.554.3611 Fax 320.554.2650

sales@massmanllc.com service@massmanllc.com www.massmanllc.com